



Testo 826-T1/T2

The **Testo 826-T1 and 825-T2** for non-contact and screening tests on food.

You can carry out the legally required checks on your food conveniently and without damaging the packaging. The adjustable alarm indicates immediately if a value has been exceeded. The TopSafe dishwasher proof protective case guarantees the hygiene of the instrument.



The Advantages:

Testo 826-T1

- Screening test - non-contact measurement, without damaging the packaging.
- Small and practical.
- Programmable upper and lower alarm limit with visual alarm.
- TopSafe and wall/belt holder included as standard.

Testo 826-T2

As above but with the additional features:

- Laser sighting to mark the location of measurement.
- Audible alarm if programmable limits exceeded.

Applications:

- Temperature screening test on food in freezers.
- Production temperature checks.
- Random checks on refrigerators.
- Incoming goods checks.

Technical Specifications

Measuring Range	-50 To +400°C
Resolution	0.5°C
Accuracy	±2°C or ±2% of measured value (the larger value applies).

Measuring Ratio	Distance:Diameter = 3:1
Emissivity Factor	0.95 (fixed)
Response Time	<2s
Wavelength	8 to 14um
Ambient Temp	0 To +50°C
Storage Temp	-40 To +70°C
Battery Type	Testo 826-T1 - 2 x 2032 Lithium Testo 826-T2 - 2 x AAA
Battery Lifetime	Testo 826-T1 - approx. 100h Testo 826-T2 - approx. 20h
Warranty	1 Year

[Main Page](#)[E-Mail To Testo](#)[Product Index](#)[Request Information](#)