

725/725Ex/726 Multifunction Process Calibrators

FLUKE®

New



Fluke 726



Fluke 725



New



Fluke 725Ex



More calibration power!

725/725Ex/726 Multifunction Process Calibrators

- Two separate channels; measure, source and view process signals simultaneously
- Measure volts, mA, RTDs, thermocouples, frequency, and resistance to test sensors and transmitters
- Source/simulate volts, mA, thermocouples, RTDs, frequency, and pressure to calibrate transmitters
- Measure or *source pressure using any of 29 Fluke 700Pxx Pressure Modules
- Source mA with simultaneous pressure measurement to conduct valve and I/P tests
- Perform fast linearity tests with auto step and auto ramp features
- Power transmitters during test using 24 V loop supply and simultaneous mA measurement
- Store frequently-used test setups for later use

726 Precision Multifunction Process Calibrator

Additional features:

- More precise measurement and calibration source performance, accuracies of 0.01%
- Transmitter error% calculation
- Memory storage for up to 8 calibration results
- Frequency totalizer and frequency pulse train source mode for enhanced flowmeter testing
- HART mode inserts 250 ohm resistor in mA measure and source for compatibility with HART instrumentation
- Integrated pressure switch test allows you to capture the set, reset and deadband of a switch
- Custom RTD curves, add calibration constants for certified RTD probes for enhanced temperature measurement

*Pressure pump required

Features

| Simultaneous Function Capability | Channel A | Channel B |
|---|-----------|-------------|
| 24.000 mA DC | M | M or S |
| 24.000 mA DC with 24 V loop supply | M | |
| 100.00 mV DC | | M or S |
| 30.000V DC Measure | M | |
| 20.000V DC Measure | | M or S |
| 10.000V DC Source | | M or S |
| 20.000V DC Source | | |
| 15 to 3200 Ohms | | M or S |
| 5 to 4000 Ohms | | |
| Thermocouple J, K, T, E, R, S, B, M, L, U, N, XK, BP | | M or S |
| RTD Cu 10, Ni120; Pt100 (392); Pt100 (JIS); Pt100, 200, 500, 1000 (385) | | M or S |
| Pressure (requires Fluke 700PXX Modules) | M | M used as S |
| Frequency; 10 kHz; (15 KHz) | | M or S |

M = Measure S = Source/Simulate
 Unique 726 features are in bold
 725Ex: ATEX certified
 (Ex ATEX II IG EEX 1a IIB 171°C)

Unique 726 features are in bold

Specifications

| Function Measure or Source | Range or Type | Resolution | Accuracy | Notes |
|----------------------------|---|--|---|---|
| Voltage | 0 to 100 mV 0 to 10V (source) 0 to 20 V (source) 0 to 30 V (measure) | 0.01 mV 0.01V 0.01 V 0.01 V | 0.01% , 0.02% Rdg + 2 LSD | Max load, 1 mA |
| mA | 0 to 24 | 0.001 mA | 0.01% ; 0.02% Rdg + 2 LSD | Max load, 725/726: 1000Ω 725Ex: 500Ω |
| mV (TC terminals) | -10.00 mV to +75.00 mV | 0.01 mV | 0.01% 0.02% of range + 1 LSD | |
| Ohms | 15Ω to 3200Ω 5Ω to 4000Ω | 0.01Ω to 0.1Ω | 0.10Ω to 1.0Ω 0.015% | |
| Hz - CPM | 2.0 to 1000 CPM 1 to 1100 Hz 1.0 to 10.0 kHz 10.0 to 15.0 kHz | 0.1 CPM 1 Hz 0.1 kHz 0.1 kHz | ±0.05% ±0.05% ±0.25% ±0.5% | Source; 5V p-p 1V - 20 V p-p squarewave, -0.1 V offset |
| Loop Supply | 725/726: 24 V DC 725Ex: 12 V DC | N/A | 10% | |
| T/C | J, K, T, E, L, N, U, XK | 0.1 °C, 0.1 °F | to 0.7 °C to 0.2 °C | |
| T/C | B, R, S, BP | 1 °C, 1 °F | to 1.7 °C to 1.2 °C | |
| RTDs | Cu (10) , Ni120 (672) Pt 100, 200, 500, 1000 (385) Pt 100 (3916), Pt 100 (3926) | 0.01 °C , 0.01 °F | to 0.15 °C | |
| | | 0.1 °C, 0.1 F | to 0.2 °C | |

Maximum voltage: 30V
Operating temperature: 10°C to 55°C
Safety: CSA C22.2 No. 1010.1:1992
 EMC: EN50082-1:1992 and EN55022:
 1994 Class B

Size (HxWxD): 200 mm x 96 mm x 47 mm
Weight: 0.65 kg
Battery: Four AA alkaline batteries.
Battery life: 25 hours typical; battery door
Warranty 725, 726: Three years
Warranty 725Ex: One year

Included Accessories

TL75 Test Leads, AC72 Test Clips, one pair of stackable test leads, user's Manuals on CD-ROM (725Ex also includes CCD control drawing, Statement of Quality Assurance Practices, NIST Traceable calibration certificate)

Ordering Information

Fluke 725 Multifunction Process Calibrator
 Fluke 725Ex Intrinsically Safe Multifunction Process Calibrator
 Fluke 726 Precision Multifunction Process Calibrator

10031-eng Rev. 07

Recommended Accessories

(Not for hazardous zones)



C125



TL220



80PK-27



TPAK



700P27