

PH METER FOR DAIRY APPLICATIONS





HI 99161

PH METER FOR DAIRY APPLICATIONS

HI 99161 is a portable, microprocessor-based pH and temperature meter specifically designed for dairy applications. Monitoring pH in dairy processes is critical to ensure a quality product.

The FC 202D pre-amplified pH electrode features a free diffusion junction that is ideal for measurements in cheese, milk and yogurt since it prevents clogging.

The HI 99161 easily fits in the palm of your hand and the bottom probe connection ensures the electrode cable doesn't get in your way. The large, multi-level LCD displays the primary reading, temperature and calibration guides simultaneously.

FEATURES

- Specialized Dairy Electrode
- Waterproof
- Multi-level LCD display

The meters display the current measurement simultaneously with the current temperature. A quickguide is also displayed to aid users in instrument operation

HOLD

The Hold button freezes readings on the display so you can easily record readings manually

 Automatic Temperature Compensation

- Automatic 1 or 2 point calibration
- BEPS

BEPS (Battery Error Prevention System) alerts the user in the event that low battery power could adversely affect readings

- Battery % displayed on startup.
- Heavy-duty

The enclosure of these waterproof meters are made of tough ABS plastic

Easy to clean and keep clean







WE DESIGN, MANUFACTURE, SUPPLY AND SUPPORT ALL OF OUR PRODUCTS.

THAT'S 360° VALUE

Over the past 30 years, **HANNA** has never failed to design fresh and innovative products and the new HI 99161 is no exception. We are excited to introduce such high accuracy and ease of use in a compact, modern design that fits right in your hand.

HANNA is the largest family-owned manufacturer of analytical instrumentation in the world. The HI 99161 is manufactured in our European state-of-the-art ISO 9001:2000 production facility and is CE compliant to EN 61326-1 and EN 61010-1 standards.

When you buy a **HANNA** product, you're not only buying the best value for your money, but you're also adding the benefit of **HANNA**'s unsurpassed customer service and post-sale technical support.

Specialized Food and Dairy pH Electrode and Starter Solutions Included!







Protective Rubber Boot
 The optional protective rubber boot helps protect your meter

Shown with HI 710021

protective boot (optional)



FC 202D PRE-AMPLIFIED pH ELECTRODE

FC 202D pH electrode features a rugged, easy to clean, PVDF body with a strong conic tip ideal for measurements in semi-solid such as meats and cheeses. The electrode is also provided with a free diffusion sleeve type reference junction which prevents the typical problems of cloqqing in viscous liquids such as milk or condiments.

The FC 202D pH electrode also incorporates a built-in temperature sensor for simultaneous pH and temperature readings, and also contains a mini amplifier to render measurements impervious to noise and electrical interferences.

· Specialized Electrode

The FC 202D is the ideal electrode to measure the pH of milk, yogurt, dairy products and semi-solid foods such as cheese

· Easy to Clean

The specialized conic tip is easy to clean and keep clean by design

SPECIFICATIONS		HI 99161	
Range	рН	-2.00 to 16.00 pH	
	Temp.	-5.0 to 105.0°C; 23.0 to 221.0°F	
Resolution	рН	0.01 pH	
	Temp.	0.1°C/0.1°F	
Accuracy (@20°C)	рН	±0.02 pH	
	Temp.	± 0.5 °C up to 60°C; ± 1 °C outside; ± 1 °F up to 140°F; ± 2 °F outside	
Temperature Compensation		Automatic	
pH Calibration		Automatic 1 or 2 point calibration with 2 sets of memorized buffers (4.01, 7.01, 10.01 or 4.01, 6.86, 9.18)	
Electrode (included)		FC 202D pre-amplified pH/temperature electrode with DIN connector and 1 m (3.3' cable)	
Battery Type		(3) 1.2V AAA	
Battery Life		Approximately 200 hours of continuous use	
Auto-off		After 8 minutes of non-use	
Environment		0 to 50°C (32 to 122°F); RH max. 100%	
Dimensions		150 x 58 x 29 mm (5.9 x 2.8 x 1.1")	

ADD	FRIA		LIEODA	ARTICAL
IIVII	PRIN	пан	инпы	4ATION

HI 99161 is supplied with FC 202D pre-amplified pH/ temperature probe with DIN connector and 1 m (3.3') cable, starter set of calibration, electrode cleaning and disinfection solution sachets, (3) 1.2V AAA batteries and instructions.

ELECTRODES

Weight

FC 202D Amplified pH electrode with built-in temperature sensor, DIN connector and 1 m (3.3') cable

SOLUTIONS

HI 5004L pH 4.01 buffer solution, 500 mL pH 7.01 buffer solution, 500 mL

 HI 5010L
 pH 10.01 buffer solution, 500 mL

 HI 7061L
 Electrode cleaning solution, 500 mL

 HI 70300L
 Electrode storage solution, 500 mL

 HI 700641P
 Electrode cleaning & disinfection solution for dairy products, (25) 20 mL sachets

 HI 700642P
 Electrode cleaning solution for cheese deposits, 20 mL sachets (25)

 HI 700640P
 Electrode cleaning solution for milk products, 20 mL sachets (25)

ACCESSORIES

HI 710020 Orange protective rubber boot Blue protective rubber boot

205q (7.2 oz.)



Recommended Operating Temperature -5 to 30° C (23 to 86° F) + 20 to 40° C (86 to 104° F)

SPECIFICATIONS	FC 202D		
Description	pH electrode		
Reference	Single, Ag/AgCl		
unction / Flow Rate	Open		
Electrolyte	Viscolene		
Max Pressure	0.1 bar		
Range	pH: 0 to 12; T: 0 to 50°C (32 to 122°F)		
Tip /Shape	Conic (6 x 10 mm)		
Temperature Sensor	Yes		
Amplifier	Yes		
Body Material	PVDF		
Connection/Cable	DIN/7-pole; 1 m (3.3')		
Recommended Use	Milk, yogurt, dairy products,		
Accommended 03c	meat, semi solid foods		

