

We measure it. **testo**

# testo 835 Pro Series Infrared Thermometers

Simplify difficult measuring tasks  
with high performance  
IR thermometers

---

50:1 long distance optics

---

4-point laser shows the exact measuring area for  
precise readings

---

High temperature range up to 2700 °F (model 835-T2)

---

Emissivity charts for accurate surface measurements

---

Contact, type K thermocouple input and wide selection  
of probe choices

---

Simple joystick operation and easy navigation icons

---

Memory and software for data management and analysis

---



°F / °C

%rH

Use the 835 IR Thermometer in trade and industry applications such as plant and facility maintenance, monitoring electrical and mechanical components, checking air conditioning and heating equipment, and practicing manufacturing and quality control or anywhere highly accurate temperature measurements are required.












The 835 thermometer is one of the most flexible and versatile IR thermometers in its class. It is extremely useful for monitoring the temperature of smaller or moving objects. It can easily access difficult to reach locations and help you measure extremely hot material at a safe distance. In addition, you can measure various different surfaces (i.e. metal, glass, ceramics) up to 2700 °F with just the press of button without adjusting or re-calibrating. Point, shoot, measure!



# Specifications

	835-T1	835-T2	835-H1
<b>Non-contact IR</b>			
Optics	50:1 (6.5 ft measuring distance)		
Laser sighting	4 point laser		
Spectral range	8 to 14 $\mu\text{m}$		
Measuring range	-22° - 1112 °F	14° - 2732 °F	-22° - 1112 °F
Accuracy	±4.5 °F (-22° to -4 °F) ±2.7 °F (-4° to 32 °F) ±1.8 °F (32° to 212 °F) 1% of rdg (rem. range)	±3.6 °F or 1% of rdg	±4.5 °F (-22° to -4 °F) ±2.7 °F (-4° to 32 °F) ±1.8 °F (32° to 212 °F) 1% of rdg (rem. range)
Resolution	0.1 °F	0.1 °F ( -14° - 1830 °F) 1 °F ( 1832 - 2732 °F)	0.1 °F
<b>Type K contact</b>			
Measuring range	-72° - 1112 °F	-72° - 1830 °F	-72- 1112 °F
Accuracy	±(-0.9 °F +0.5% rdg)		
Resolution	0.1 °F		
<b>Testo humidity sensor</b>			
Measuring range	-	-	0 to 100% rH
Accuracy	-	-	±2 %rH
Resolution	-	-	1.8 °F 0.1 %rH 0.1 °Ftd
<b>General technical data</b>			
Emissivity	0.10 to 1.00 (steps 0.01)		
Emissivity table	20 values on board		
Laser spot	On / Off		
Memory hi/lo limit	200 values		
Alarm (max / min values)	IR / TC temperature		
Alarm signal	Audible (optional)		
Operating temperature	-4° - 122 °F		
Dimensions	7.6 x 6.5 x 2.5 in		
Weight	1 lb		
Battery	3 AA (or USB operating with PC-Software)		
Battery life	25 hr (w/o laser and backlight) 10 hr (w/o backlight)		
Auto OFF	Backlight: 30 secs Instrument: 120 secs.		
Warranty	2 years		

# Probes

Probe type	Dimensions (shaft and probe tip)	Measuring range	Accuracy	t (secs)	Part no.
Air probe, TC type K, 4 ft. cable		-76° - 752 °F	Class 2	25	0602 1793
Immersion probe, water-proof, TC type K, 4 ft. cable		-76° - 1832 °F	Class 1	2	0602 0593
Immersion/penetration probe, waterproof, TC type K, 4 ft. cable		-76° - 1472 °F	Class 1	3	0602 2693
Immersion/penetration probe, waterproof, 4 ft. cable		-76° - 752 °F	Class 2	7	0602 1293
Surface probe, spring TC, type K, 4 ft cable		-76° - 572 °F	Class 2	3	0602 0393
Surface probe (paddle) TC type K		32 ° - 572 °F	Class 2	5	0602 0193
Surface probe w/bend, spring TC, type K, 4 ft. cable		-76° - 572 °F	Class 2	3	0602 0993
Surface probe, waterproof, small flat probe head, TC type K, 4 ft cable		-76° - 1832 °F	Class 1	20	0602 0693
Magnetic probe for metal surfaces, TC type K, 5 ft. cable		-58° - 752 °F	Class 2		0602 4892
Pipe wrap probe w/ velcro (5"), TC type K, 5 ft. cable		-58° - 248 °F	Class 1	90	0628 0020
Pipe wrap probe w/ adjustable head (0.2 to 2.5") TC type K, 4 ft. cable		-76° - 266 °F	Class 2	5	0602 4592

## Ordering data

### testo 835-T1 Standard

testo 835-T1, IR thermometer, 4-point laser sighting, data logging, and external probe input incl. batteries and calibration protocol



Part no. 0560 8351

### testo 835-T2 High Temperature

testo 835-T2, IR thermometer, 4-point laser sighting, data logging, and external probe input, incl. batteries and calibration protocol



Part no. 0560 8352

### testo 835-H1 Moisture Module

testo 835-H1, IR thermometer, 4-point laser sighting, data logging, and external probe input, humidity module, incl. batteries and calibration protocol



Part no. 0560 8353

Accessories	Part no.
Bracket	0440 0950
USB cable for PC	0449 0047
Adhesive tape (1 roll) 32 ft.	0554 0051
Silicone heat paste (max. 500 °F)	0554 0004
NIST Temperature Calibration for IR Thermometer	400520 1911

12\_TES\_XXXX

Subject to change without notice.

Testo, Inc  
 40 White Lake Rd.  
 Sparta, NJ 07871  
 800-227-0729  
 Fax -862-354-5020  
 email: info@testo.com

[www.testo.com](http://www.testo.com)