

Vane anemometer

testo 417 – With built-in vane

Measurement of flow velocity, volume flow and temperature

Recognition of flow direction

Point and timed mean value calculation

Max./min. values

Hold button for freezing measurement value

Display illumination

Auto-off function



m/s

°C

testo 417 is a compact, large-area anemometer with a built-in flow velocity / temperature vane. It measures flow velocity, volume flow and temperature. Thanks to the integrated measurement with the 100 mm vane, it is ideally suited for measurements at air input and output vents. The flow direction, i.e. blowing or sucking flow, is visible in the display. The optimum funnel set additionally allows measurements on ventilation grilles and disc outlets.

The volume flow is directly shown in the display. For the purposes of volume flow calculation, the duct area can be easily entered into the testo 417. In addition to this, the instrument can be switched over to display the current temperature.

Timed and point mean value calculation provide information on the average volume flow, flow velocity and temperature measurement value. The Hold function allows the current measurement value to be frozen in the display, min./max. values are also displayed at the press of a button.

Technical data / Accessories

testo 417

testo 417 vane anemometer with integrated 100 mm vane incl. temperature measurement, battery and calibration protocol

Part no. 0560 4170



General technical data

| | |
|-----------------------|------------------------|
| Storage temperature | -40 to +85 °C |
| Operating temperature | 0 to +50 °C |
| Battery type | 9V block battery, 6F22 |
| Battery life | 50 h |
| Weight | 230 g |
| Dimensions | 277 x 105 x 45 mm |
| Housing material | ABS |
| Warranty | 2 years |

Sensor types

| | NTC | Vane | Volume flow |
|-------------------|-------------|--------------------------|--|
| Measuring range | 0 to +50 °C | +0.3 to +20 m/s | 0 to +99999 m ³ /h |
| Accuracy ±1 digit | ±0.5 °C | ±(0.1 m/s +1.5% of m.v.) | |
| Resolution | 0.1 °C | 0.01 m/s | 0.1 m ³ /h (0 to +99.9 m ³ /h) 1 m ³ /h (+100 to +99999 m ³ /h) |

Accessories for measuring instrument

Part no.

| Accessories for measuring instrument | Part no. |
|---|-----------|
| Case for measuring instrument and probes | 0516 0210 |
| testovent 417 funnel set for plate outlets (Ø 200 mm) and funnel for ventilator (330 x 330 mm) | 0563 4170 |
| Flow straightener testovent 417 | 0554 4172 |
| Recharger for 9V rechargeable battery for external recharging of 0515 0025 battery | 0554 0025 |
| 9V rech. battery for instrument instead of battery | 0515 0025 |
| DAkkS calibration certificate velocity, hot wire, vane anemometer; calibration points 0.5; 1; 2; 5; 10 m/s | 0520 0244 |
| ISO calibration certificate velocity, hot wire, vane anemometer, Pitot tube; calibration points 1; 2; 5; 10 m/s | 0520 0004 |
| ISO calibration certificate velocity, hot wire, vane anemometer, Pitot tube; calibration points 5; 10; 15; 20 m/s | 0520 0034 |
| ISO calibration certificate velocity, hot wire, vane anemometer; calibration points 0.3; 0.5; 0.8; 1.5 m/s | 0520 0024 |

Testo Inc.
40 White Lake Rd.
Sparta, NJ 07871
800-227-0729
Email: info@testo.com