

Model: DT- 320**کلمپ قابل انعطاف جریان بانمایشگر**

EMC& LVD
EN : 61326
EN : 61010-1
EN : 61010-02-031



قابلیت اندازه گیری :

محدوده اندازه گیری :

جریان : 0 ~ 3000 A AC

قطر هادی: 150 Ø

دیگر قابلیت ها :

طراحی ارگونومیک

چراغ پس زمینه نمایشگر

حافظه مینیمم / ماکزیمم / Data Hold مقادیر

Model: DT- 320 B**سنسور کلمپ قابل انعطاف جریان بار**

EMC& LVD
EN : 61326
EN : 61010-1
EN : 61010-02-031



قابلیت اندازه گیری :

محدوده اندازه گیری :

جریان: 0 ~ 3000 A AC

قطر هادی: 150 Ø

دیگر قابلیت ها

طراحی ارگونومیک

کلید انتخاب رنج ۳۰، ۳۰۰، ۳۰۰۰ آمپر

Features (DT - 320)

18 " (457mm) head cable length
3000A AC current measurement
Auto ranging
Data Hold & MAX/MIN
3000 count large scale LCD display with backlit
7.5mm coil diameter for tight space measurement
Indicator low battery
Ergonomically designed one hand operation
CAT IV 600V/CAT III 1000V safety standard

Features (DT - 320 B)

18 " (457mm) head cable length
3000A AC current measurement
Slide switch to change range
Voltage output to universal voltage meters
7.5mm coil diameter for tight space measurement
2 meter extension cable
Low Bart. LED indicator
Ergonomically designed one hand operation
CAT IV 600V/CAT III 1000V safety standard

**Specification (DT - 320)**

Function	Max Range	Resolution	Basic Accuracy
AC Current	30.00A AC	0.01A	± (8 + %3.0d)
400~50Hz	300.0A AC	0.1A	± (5 + %3.0d)
True RMS	3000A AC	1A	± (5 + %3.0d)

Specification (DT - 320 B)

Function	Max Range	Best Measurement Range	Basic Accuracy	Output Voltage
AC Current	30 A AC	≤30.00A	100mV/A	± %3.0
400~50Hz	300 A AC	30.0A300.0-A	10mV/A	± %3.0
True RMS	3000 A AC	300A3000-A	1mV/A	± %3.0

Size(HxWxD): 180 mm x 106 mm x 26 mm

Weight: 200 g

Accessories:

Gift box with carrying case, 1.5V AAA x 2 batteries

Size(HxWxD): 180 mm x 106 mm x 26 mm

Weight: 210 g

Accessories:

Gift box with carrying case, 1.5V AAA x 2 batteries