

The 3370B series clamp meters offer all the features you need to fit the way you work. The bodies and jaws fit perfectly in your hand and into tight places. Meter controls are positioned so that current measurements can be done with one hand. A large backlit display (on most models) is easy to see and a handy Display Hold keeps measurements on the display.



EMC & LVD  
EN: 61326  
EN: 61010-1,  
EN: 61010-02-031

- Double molded plastic housing
- True RMS measurement for ACV & ACA

Drop-proof to 2M

True RMS



Features

	3370B	3371B	3372B	3373
Current measurement	AC	AC/DC	AC/DC	AC/DC
LCD display counts	4000	4000	6000	6000
AC True RMS	*	*	*	*
Display with backlight	*	*	*	*
Data Hold & Peak Hold	*	*	*	*
Max./Min	*	*	*	*
REL. (Zero) Function	*	*	*	*
Auto Power Off	*	*	*	*
Low battery indication	*	*	*	*
Analog Bargraph / 61 seg.	* / 41 seg.	* / 41 seg.	*	*
1.9" (48mm) Jaw opening	*	*	*	*
NCV Detection & flashlight	*	*	*	*
Inrush Current	*	*	*	*

Specifications

Function	Max Range	Basic Accuracy	3370B	3371B	3372B	3373
Voltage DC	1000V	±(0.5%+1d)	600V	600V	*	*
Voltage AC	1000V	±(1.5%+2d)	600V	600V	*	*
Current DC	1000A	±(2.0%+5d)	*	*	*	*
Current AC	1000A	±(2.5%+4d)	*	*	*	*
Resistance	60MΩ	±(3.0%+5d)	40M	40M	*	*
Temperature	1000°C/ 1832°F	±(3.0%+3d)	*	*	*	±(1.0%+3d)
Capacitance	10mF	±(2.5%+5d)	4000µF	4000µF	6mF	6000µF
Frequency	10MHz	±(1.2%+2d)	*	10kHz	*	10MHz
Inrush Current	1000A	±(1.5%+2d)	*	*	*	*
Continuity check	Buzzer sounds at 50Ω					
Diode test	Test current 0.3mA					

Size(HxWxD): 230mm x 76mm x 40mm

Weight: 315g

Accessories:

Test leads, gift box with carrying case, Temperature probe and 9V battery.  
Software(3373)



Model 3371B



Model 3372B



The 3385 series clamp meters offer all needed features for measurement, design for perfectly hand-hold and tight place testing. A large backlit display (on most models) is easy to see and a handy Display Hold keeps measurements on the display. Flexible current probe expands the measurement range to 2500 ACA.



EMC & LVD  
EN: 61326  
EN: 61010-1,  
EN: 61010-02-031

- Double molded plastic housing
- True RMS measurement for ACV & ACA
- Flexible current probe expands the measurement range to 2500 ACA for all models
- Dual type K inputs for temperature measuring support more application.(3387/3388)
- Flexible current probe expands the measurement range to 2500 ACA



Drop-proof to 2M

True RMS

Features

	3385	3386	3387	3388
Current measurement	AC	AC/DC	AC	AC/DC
LCD display counts	50000	50000	50000	50000
2500A ACA Flexible clamp	*	*	*	*
AC True RMS	*	*	*	*
Dual type K inputs	*	*	*	*
Display with backlight	*	*	*	*
Data Hold & Peak Hold	*	*	*	*
Max./Min	*	*	*	*
REL. (Zero) Function	*	*	*	*
Auto Power Off	*	*	*	*
Low battery indication	*	*	*	*
1.9" (48mm) Jaw opening	*	*	*	*
NCV Detection	*	*	*	*
Bluetooth interface	*	*	*	*

Specifications

Function	Max Range	Basic Accuracy	3385	3386	3387	3388
Voltage DC	600V	±(0.1%+4d)	*	*	*	*
Voltage AC	600V	±(1.0%+3d)	*	*	*	*
Current DC	1000A	±(2.3%+5d)	*	*	*	*
Current AC	1000A	±(2.3%+5d)	*	*	*	*
DC µA/mA Current	5000.0µA/500.00mA	±(1.0%+3d)	*	*	*	*
AC µA/mA Current	5000.0µA/500.00mA	±(1.5%+3d)	*	*	*	*
Resistance	50MΩ	±(3.0%+5d)	*	*	*	*
Temperature	1000°C/ 1832°F	±(1.0%+2.5°C/4.5°F)	*	*	*	*
Capacitance	5mF	±(3.3%+10d)	*	*	*	*
Frequency	10MHz	±(0.3%+2d)	*	*	*	*
ACA Flexible clamp	2500A	±(3.3%+10d)	*	*	*	*
Continuity check	Buzzer sounds at 35Ω					
Diode test	Test current 0.3mA					

Size(HxWxD): 230mm x 78mm x 40mm

Weight: 315g

Accessories:

Test leads, gift box with carrying case, Temperature probe and 9V battery.  
Software(3387/3388)



Model 3386



Model 3388