

Cond 7 Vio

- Resolution 0,01 μ S
- Automatic and manual **temperature compensation**
- Coloured backlit high definition **LCD display**
- **Automatic calibration** on 4 standard points and 1 custom
- 3 selectable **cell constants**

MAIN FEATURES

Professional portable conductivity meter with innovative **backlit high definition coloured LCD display**, suitable to work in any conditions, thanks also to the possibility to adjust automatically and manually contrast and brightness of the display.

The **step by step guide** in setup and calibration mode allows a simple and intuitive use of the device.

Automatic calibration of conductivity up to 4 points and 1 point custom defined by the user.

Adjustable reference temperature and selectable cell constant.

Indication with icons of the calibrated points.

Measurement **stability indicator** and possibility of selecting 3 levels of stability.

All operations and errors are constantly monitored and shown to the operator via the **coloured LED** above the display.



Measuring range:

Cond: 0,1 μ S ... 200 mS (0,01 μ S - automatic)

TDS: 0,01 mg/l ... 200,0 g/l

Temperature: 0 ... 100,0 (0,1 °C)



Cond 7 Vio Kit

Equipped with:

Conductivity standard, user manual and carrying case.

	Name	Description	p/n
NEW	COND 7 VIO WITH CELL	Complete with conductivity cell EPT 1 with temperature sensor integrated. 1 m cable	50110442
	COND 7 VIO WITH CELL	Complete with conductivity cell 2301T with temperature sensor integrated. 1 m cable	50110412
	COND 7 VIO WITHOUT CELL	With accessories, without conductivity cell	50110422