

## Specifications HI98100 Checker®Plus

Specifications		THISOTOO CHECKET THUS
рН	Range	0.00 to 14.00 pH
	Resolution	0.01 pH
	Accuracy (@25°C/77°F)	±0.2 pH
Additional Specifications	Calibration	automatic, two-point
	Electrode	HI1271 (included)
	Battery Type / Life	CR2032 Li-ion / approximately 1000 hours of continuous use
	Auto-off	8 minutes
	Environment	0 to 50°C (32 to 122°F); RH 95% max
	Dimensions	71 x 50 x 21 mm (2.8 x 2.0 x .77") (excluding probe)
	Weight	50 g (1.8 oz.)
Ordering Information	HI98100 (Checker®Plus) is supplied with pH electrode, battery and instructions.	

For a list of our pH calibration and electrode solutions, see section 3

## Checker®Plus pH Tester

- High accuracy with 0.01 pH resolution
- Two-point calibration with automatic buffer recognition
- 1000 hours of battery life
- HI1271 small diameter probe fits easily into a test tube

The pH Checker®Plus series provides users with fast and accurate readings from 0 to 14 pH with a resolution of 0.01 pH. The Checker®Plus features an easy-to-read LCD and two-point calibration with automatic buffer recognition.

The HI1271 pH electrode of the Checker®Plus can be easily replaced. You only need to unscrew the electrode from the meter body and screw on a new one.

The Checker®Plus is fast, accurate and lightweight. With 1000 hours of battery life, there is no need to worry about frequent battery replacement.



- Easy battery access
  - Easily remove the battery cover to replace the battery
- Save battery life with auto-off
  - With the auto-off feature, the Checker®Plus shuts off after 8 minutes

