



*All-steel construction.

*The 45-tooth reversible ratchet head for both clockwise and counterclockwise operation.

*+/-4% accuracy in clockwise direction exceeds international specifications.

*Unique, stay-in-place, Lock Ring makes adjustments easier and secures selected torque from accidental change.

*Metric scale with fine increments and reference English scales are easy to read and set.

*The identity code marked on each wrench makes it possible to keep accurate records.

*Non slip grooved handle.

Part Code	Drive	Torque Range		Length mm	Width mm	Weight kg
		N.m	Lb.ft			
GM112	1/4"	2.5-12	20-105*	290	38	0.68
GM120	1/4"	4.0-20	30-180*	290	38	0.68
GM230	3/8"	6.0-30	50-250*	318	38	0.82
GM330	1/2"	6.0-30	50-250*	318	38	0.82
GM260	3/8"	10-60	9-45	388	38	0.96
GM360	1/2"	10-60	9-45	388	38	0.96
GM2125	3/8"	25-125	20-90	443	38	1.04
GM3125	1/2"	25-125	20-90	443	38	1.04
GM3200	1/2"	40-200	30-150	468	40	1.16
GM3335	1/2"	65-335	50-250	528	40	1.30
GM4335	3/4"	65-335	50-250	528	40	1.34
GM3335L	1/2"	65-335	50-250	700	40	2.10
GM4335L	3/4"	65-335	50-250	700	40	2.15
GM4400	3/4"	80-400	60-300	700	57	2.95
GM4500S	3/4"	100-500	80-400	700	57	2.95
GM4500	3/4"	100-500	80-400	855	60	5.00
GM4800	3/4"	160-800	120-600	1055	60	5.90
GM5800	1"	160-800	120-600	1055	60	5.90
GM41000	3/4"	200-1000	150-750	1055	60	5.90
GM51000	1"	200-1000	150-750	1055	60	5.90
GM51500	1"	300-1500	200-1100	1260	72	9.20
GM52000	1"	400-2000	300-1500	1260	72	9.20
GM53000	1"	600-3000	400-2000	1260	72	10.50

*Unit is Lb.in