Dissolved Oxygen

2

CE

Portable D.O. Meter for Field Applications

Mi605 is a portable, microprocessor-based, Dissolved Oxygen meter with automatic calibration and temperature compensation (ATC) specifically designed for spot sampling applications.

Dissolved Oxygen measurements can be displayed in parts per million (ppm=mg/L) or in % of saturation. The temperature is indicated in Celsius from 0 to 50° C

with 0.1 resolution. The meter compensates salinity and altitude automatically after manual input.

Calibration is very simple and fast: just expose the polarographic Dissolved Oxygen probe MA840, supplied with the instrument, to air and press the CAL button. No need for chemical solutions!

A HOLD button allows the user to freeze the reading on the LCD.

The low battery indicator and the easy to replace screw on cap membranes make the Mi605 a compact instrument and ideal for all applications: aquaculture, wastewater, environmental and educational.

Specifications	Mi605	
Range O ₂ % Saturation O ₂ Temp	0.0 to 45.00 mg/L (ppm) 0.0 to 300% 0.0 to 50.0°C / 32 to 122°F	
Resolution 02 % Saturation 02 Temp	0.01 mg/L (ppm) 0.1% 0.1°C	WW
Accuracy O ₂ % Saturation O ₂ Temp	±1.5% Full Scale ±1.5% Full Scale ±0.5°C	
Typical EMC O ₂ Deviation % Saturation O ₂ Temp	±0.3 mg/L (ppm) ±3.5% ±0.5°C	
Calibration	automatic in saturated air	
Temperature Compensation	automatic, from 0 to 50°C / 32 to 122°F	AAA
Altitude Compensation	0 to 4000 m; 100 m resolution	11 A A A
Salinity Compensation	0 to 80 g/L; 1 g/L resolution	
Probe	MA840 (included)	
Environment	0 to 50°C / 32 to 122°F; max RH 100%	
Battery Type	1 x 9V alkaline (included)	
Battery Life	approx. 100 hours of use	
Auto-off	after 4 hours of non-use	
Packaging dimensions	305 x 280 x 115 mm	
Packaging weight	1.44 kg	- 12 h

30

Mi 605 Dissolved Oxygen meter

RANGE

ACTO

CAI

Milwaukee

Hard Carrying Case

Mi605 is supplied complete in a hard carrying case complete with a D.O. probe, spare membranes, calibration solutions, battery and instructions.



Accessories

MA9071Refilling Electrolyte solution, 230 mL bottleMA841Spare membrane (5 pcs)MA840D.O. Probe

Ordering Information

Mi605 is supplied complete with MA840 polarographic D.O. probe with 4 meters cable, 2 spare membranes, 20 mL bottle of electrolyte solution, rugged carrying case, 9V battery and instructions.

weiter

www.seeanco.com_021-47627010

