



technical data:

Specifications:	
Pressure range:	368/725 PSI low/high sides (25/50 Bar)
Pressure resolution:	0.1 PSI (0.1 Bar)
Pressure overload:	735/1470 PSI low/high sides (50/100 Bar)
Line temperature input:	2, Pt 100 (standard), +2 wireless (option)
Temperature measurement range:	-58 to 392°F (-50 to 200°C)
Temperature resolution:	0.1°F (0.1°C)
Pre-loaded refrigerants:	30 plus choice of 10 more from testo.com via EasyKool download

specifications:

Description:	
Dimensions:	10.25" x 5" x 2.75"
Housing:	NEMA 3/3S(IP54)
Battery:	4AA (40 hrs. w/o backlight)
Display size:	2" x 3", white LED
Weight:	2.7 lbs.
Warranty:	2 years unit

ordering information:

556 Advanced RSA Kit with Wireless Probe: analyzer, software and USB cable, wireless pipe-clamp probe, 9.5' pipe-clamp temperature probe, power supply lock for carabiner hook, EasyKool PC software and carrying case

part no. 400563 5562

560 Advanced RSA Kit with Micron Measurement: analyzer w/ micron sensor, software and USB cable, 9.5' pipe-clamp temperature probe, power supply, lock for carabiner hook, EasyKool PC software and carrying case

part no. 400563 5606



Visit www.testousa.com/523 and download our **FREE AC/Refrigeration Application Guide** today. It's filled with in-depth and practical application knowledge for today's technicians.

Ask about new ammonia compatible versions.

Distributor: