

# ACCESSORIES



## UT-F/UT-L SERIES CARTRIDGE FUSE/TEST LEADS



**UT-F01 Cartridge fuse (fast fuse porcelain tube)**

- Specifications:  $\Phi 6.35 \times 31.8$  500mA/600V
- Brand: HOLLY
- Safety certificate: CE
- Suitable products: UT61(GS) series, UTD1050CL, UT1939B, UT125C
- Amount: 1PC



**UT-F03 Cartridge fuse (fast fuse porcelain tube)**

- Specifications:  $\Phi 6.35 \times 31.8$  0.5A/1000V
- Brand: HOLLY
- Safety certificate: TUV
- Suitable products: UT71 series, UT81B, UT81C, UT801, UT802, UT505B
- Amount: 1PC



**UT-F05 Cartridge fuse (fast fuse porcelain tube)**

- Specifications:  $\Phi 6.35 \times 31.8$  600mA/600V
- Brand: HOLLY
- Safety certificate: TUV
- Suitable products: UT139C, UT139E, UT139S
- Amount: 1PC



**UT-F07 Cartridge fuse (fast fuse porcelain tube)**

- Specifications:  $\Phi 10.3 \times 38$  10A/1000V
- Brand: HOLLY
- Safety certificate: CCC, UR/CUR, VDE
- Suitable products: UT61 series(2010 CE), UT71(CE), UT171A/B/C, UT181A, UT801, UT802, UT803, UT804, UT805A
- Amount: 1 PC



**UT-F10 Cartridge fuse (fast fuse porcelain tube)**

- Specifications:  $\Phi 6.35 \times 31.8$  800mA/1000V
- Brand: HOLLY
- Safety certificate: UL
- Suitable products: UT171 series, UT181A
- Amount: 1PC



**UT-F02 Cartridge fuse (fast fuse porcelain tube)**

- Specifications:  $\Phi 6.3 \times 25.4$  10A/600V
- Brand: BUSSMANN
- Safety certificate: UL
- Suitable products: UT139 series, UT133A/B
- Amount: 1PC



**UT-F04 Cartridge fuse (fast fuse porcelain tube)**

- Specifications:  $\Phi 6 \times 32$  0.2A/600V
- Brand: HOLLY
- Safety certificate: TUV
- Suitable products: UT139A, UT105
- Amount: 1PC



**UT-F06 Cartridge fuse (fast fuse porcelain tube)**

- Specifications:  $\Phi 6.35 \times 31.8$  10A/600V
- Brand: HOLLY
- Safety certificate: TUV
- Suitable products: UT105, UT81B, UT81C
- Amount: 1PC



**UT-F08 Cartridge fuse (fast fuse porcelain tube)**

- Specifications:  $\Phi 6.35 \times 31.8$  600mA/1000V
- Brand: HOLLY
- Safety certificate: TUV
- Suitable products: UT61 series, UT8803E, UT61A/B/C/D/E-US
- Amount: 1PC



**UT-L01 Tweezers test leads**

- Length: 450mm, Probe length: 5mm
- Safety level: CAT III 1000V
- Application: SMT components measurement, universal test leads
- Amount: 1PC

## UT-L SERIES TEST LEADS



### UT-L02 BNC alligator clip test leads

- Length: 1000mm, Clip opening: 3mm
- Safety level: CAT II 600V 2A
- Application: BNC connector for instrument inputs
- Amount: 1PC



### UT-L06 Dual head connectors

- Length: test leads 1200mm
- Safety level: CAT III 1000V 10A
- Application: Multifunctional connectors, all multimeters and clamps
- Amount: 1 pair



### UT-L07 Probes

- Length: 1000mm, Probe length: 5mm+12mm
- Temperature condition: -15°C~40°C
- Safety level: CAT III 1000V 10A
- Features and application: Double insulated, lantern probes, removable probe protector, general type probes, all multimeters and clamps measuring within spec
- Amount: 1 pair



### UT-L09 Dual head connectors

- Length: 1000mm, one head is 180°, the other is 90°
- Temperature condition: -15°C~40°C
- Safety level: CAT III 1000V 10A
- Features and application: Double insulated, banana plug with security mask and standard diameter, suitable for multiple devices, all multimeters and clamps
- Amount: 1 pair



### UT-L10 Dual head multifunctional connectors

- Length: 1000mm, ø4mm
- Temperature condition: -15°C~40°C
- Safety level: CAT III 1000V 10A
- Features and application: Banana plug, used for testing adapter cables
- Amount: 1 pair



### UT-L13 Probes

- Leads length: 1200mm, Rod length: 128mm
- Tip length: 18mm, with ø4mm standard lantern tip
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Temperature condition: -15°C~40°C
- Features and application: Double insulated UL authenticated material, ø4mm standard lantern-tip probe, which can be connected to standard alligator clips and test leads, removable tip shield sleeve, general type probes
- Amount: 1 pair



### UT-L16 Probes

- Length: 1200mm, Rod length: 133mm
- Tip length: 18mm
- Safety level: CAT III 1000V 16A
- Safety certificate: EN 61010-031 :2015
- Features and application: Double insulated silicone wire material, through hole type input terminal, general type probes, all multimeters and clamps measuring within spec
- Amount: 1 pair



### UT-L17 Probe with LED light

- leads length: 1000mm
- Tip length: 16mm
- Safety level: CAT II 1000V 10A
- Features and application: Controllable LED light source, all multimeters and clamps measuring within spec
- Amount: 1PC

## UT-L SERIES

### TEST LEADS



#### UT-L20 Probes

- Leads length: 900mm, Rod length: 101mm
- Tip length: 16.5mm
- Safety level: CAT I 1000V/CAT II 600V 10A
- Features and application: Cross plug with shield sleeve, general type probes, all multimeters and clamps measuring within spec
- Amount: 1 pair



#### UT-L21 Probes

- Leads length: 900mm, Rod length: 133mm
- Tip length: 15.8mm
- Safety level: CAT III 1000V/CAT IV 600V 20A
- Features and application: Cross plug with shield sleeve, general type probes, all multimeters and clamps
- Amount: 1 pair



#### UT-L25 Probes

- Leads length: 900mm, Rod length: 115mm
- Tip length: 18mm
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Safety certificate: EN 61010-031 2015
- Features and application: Double insulated wire, removable tip shield sleeve, general type probes, all multimeters and clamps measuring within spec
- Amount: 1 pair



#### UT-L26 Probes

- Leads length: 900mm, Rod length: 136mm
- Tip length: 15.7mm
- Safety level: CAT III 1000V/CAT IV 600V 20A
- Safety certificate: EN 61010-031 2015
- Features and application: UL 16AWG double insulated wire, removable tip shield sleeve, cross type input terminal with full protection, general type probes, all multimeters and clamps
- Amount: 1 pair



#### UT-L27 Probes

- Leads length: 900mm, Rod length: 130mm
- Tip length: 16.3mm, threaded
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Safety certificate: EN 61010-031 2015
- Features and application: Double insulated UL authenticated material, removable tip shield sleeve, banana plug input terminal, general type probes, all multimeters and clamps measuring within spec
- Amount: 1 pair



#### UT-L28 Probes

- Leads length: 900mm, Rod length: 128mm
- Tip length: 16.8mm
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Features and application: Double insulated wire, removable tip shield sleeve, banana plug input terminal, general type probes, all multimeters and clamps measuring within spec
- Amount: 1 pair



#### UT-L29 Probes

- Leads length: 900mm, Rod length: 136mm
- Tip length: 15.7mm
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Safety certificate: EN 61010-031 2015
- Features and application: Double insulated UL authenticated material, through hole crosshead with full protection input, removable tip shield sleeve, general type probes, all multimeters and clamps measuring within spec
- Amount: 1 pair



#### UT-L30 Probes

- Leads length: 900mm, Rod length: 136mm
- Tip length: 15.7mm
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Safety certificate: EN 61010-031 2015
- Features and application: Double insulated UL authenticated material, removable tip shield sleeve, cross input terminal, general type probes, all multimeters and clamps measuring within spec
- Amount: 1 pair



## UT-L SERIES TEST LEADS



### UT-L31 Probes

- Line length: 1300mm
- Tip length: 18.5mm
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Features and application: rod with switch, removable tip shield sleeve, used for UT505B
- Amount: 1PC



### UT-L33 Group test leads

- Combinations: combined with 1PCS (red+black) alligator clip test leads and 1PCS double-plug alligator clip test leads
- Material: Double insulated UL authenticated material
- Total length: 1200±20mm
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Application: UT511
- Amount: 1 Group



### UT-L35 Group test leads

- Combination: (1) 1.6m test lead (green+red) 1pair (2) 5m green test lead 1PCS (3) 10m yellow test lead 1PCS (4) 20m red test lead 1PCS
- Material: UL authenticated material
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Application: UT521、 UT522、 UT572
- Amount: 1 Group



### UT-L37 Dual through hole test leads

- Material: Double insulated wire, 102 cores
- Length: 1090mm
- Safety level: CAT III 1000V/CAT IV 600V
- Application: UT500 series、 UT531
- Amount: 1 pair



### UT-L39 Alligator clip test leads with shield sleeve

- Material: Double insulated wire
- Length: 1000±50mm
- Features and application: Adapter plug with BNC
- Amount: 1PC



### UT-L32 Group test leads

- Combinations: combined with 2PCS test leads, (red+black) and (yellow+blue)
- Material: Double insulated leads
- Line length: 1090mm
- Safety level: CAT III 600V/CAT IV 300V
- Application: UT233、 UT243
- Amount: 1 Group



### UT-L34 Group test leads

- Combinations: combined with 1PCS green, 1PCS black and 1PCS red alligator clip test leads
- Total length: 1500±20mm
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Application: UT513、 UT513A
- Amount: 1 Group



### UT-L36 Dual through hole test leads

- Material: 18AWG UL authenticated material
- Length: 1100mm
- Safety level: CAT III 1000V/CAT IV 600V
- Application: UT505B
- Amount: 1 pair



### UT-L38 Group test leads

- Material: Double insulated wire, 102 cores Length: 1090mm
- Safety level: CAT III 600V/CAT IV 300V
- Features and application: with buckle, used for UT261A、 UT261B
- Amount: 3PCS



### UT-L40 SMD patch clamp

- Leads length: 450mm, probe length: 5mm
- Temperature condition: -10°C~40°C
- Safety level: CAT II 1000V 2A
- Features and application: used to SMT components, for UT611、 UT612
- Amount: 1PC

## UT-L/UT-H/UT-P SERIES TEST LEADS/PROBES



### UT-L41 Alligator clip short test leads

- Core: 19/20
- Length: 110-130mm
- Features and application: full protection cross input terminal, used for UT71 series, UT801, UT802, UT803, UT601, UT603
- Amount: 1 pair



### UT-L42 Kelvin clip double insulated wire

- Length: 1000mm
- Features and application: AV input lead, used for UT620A, UT620B
- Amount: 1 pair



### UT-L43 RS232C interface wire

- Length: 1000mm
- Features and application: Dual head 9-pin interface, used for UT803, UT804, UT805A
- Amount: 1PC



### UT-L45 BNC-BNC through leads

- Material: 50Ω coaxial cable
- Length: 1000mm
- Features and application: dual-head BNC interface, used for UTG2025A, UTG4162A, UTG4122A, UTG4082A, UTG1010A, UTG1005A, UTG2122B, UTG2082B, UTG2062B
- Amount: 1PC



### UT-L46 Four-wire test probes

- Leads material: 182-core double shielded wire
- Leads length: 1000mm
- Application: UT620B
- Amount: 1pair



### UT-L61 Kelvin test leads

- Leads material: Double insulated wire
- Leads length: 600mm
- Application: UT611, UT612
- Amount: 1pair



### UT-H01 Passive probe 25MHz

- Probe factor: (1:1/10:1)
- Bandwidth: 25MHz
- Input resistance: 1×:1MΩ±2%, 10×:10MΩ±2%
- Working voltage: 1×:300Vpp, 10×:600Vpp
- Application: UTD1025CL, UTD1025C (only for handheld type)
- Amount: 1PC



### UT-H03 Passive probe 60MHz

- Probe factor: (1:1/10:1)
- Bandwidth: 60MHz
- Input resistance: 1×:1MΩ±2%, 10×:10MΩ±2%
- Working voltage: 1×:300Vpp, 10×:600Vpp
- Application: UTD1050CL, UTD1062C (only for handheld type)
- Amount: 1PC



### UT-H04 Passive probe 100MHz

- Probe factor: (1:1/10:1)
- Bandwidth: 100MHz
- Input resistance: 1×:1MΩ±2%, 10×:10MΩ±2%
- Working voltage: 1×:300Vpp, 10×:600Vpp
- Application: UTD1000 series (only for handheld type)
- Amount: 1PC



### UT-H05 Passive probe 200MHz

- Probe factor: (1:1/10:1)
- Bandwidth: 200MHz
- Input resistance: 1×:1MΩ±2%, 10×:10MΩ±2%
- Working voltage: 1×:300Vpp, 10×:600Vpp
- Application: UTD1000 series (only for handheld type)
- Amount: 1PC

## UT-V/UT-P SERIES PROBES



**UT-P01 Passive probe 25MHz**

- Probe factor: (1:1/10:1)
- Bandwidth: 25MHz
- Input resistance: 1×:1MΩ±2%, 10×:10MΩ±2%
- Working voltage: 1×:300Vpp, 10×:600Vpp
- Application: UTD2025CL
- Amount: 1PC



**UT-P03 Passive probe 60MHz**

- Probe factor: (1:1/10:1)
- Bandwidth: 60MHz
- Input resistance: 1×:1MΩ±2%, 10×:10MΩ±2%
- Working voltage: 1×:300Vpp, 10×:600Vpp
- Application: UTD2052CL, UTD4062C, UTD4042C
- Amount: 1PC



**UT-P04 Passive probe 100MHz**

- Probe factor: (1:1/10:1)
- Bandwidth: 100MHz
- Input resistance: 1×:1MΩ±2%, 10×:10MΩ±2%
- Working voltage: 1×:300Vpp, 10×:600Vpp
- Application: UTD4082C, UTD4102C, UTD4104C, UTD4102CM, UPO2102CS, UPO2104CS
- Amount: 1PC



**UT-P05 Passive probe 200MHz**

- Probe factor: (1:1/10:1)
- Bandwidth: 200MHz
- Input resistance: 1×:1MΩ±2%, 10×:10MΩ±2%
- Working voltage: 1×:300Vpp, 10×:600Vpp
- Application: UTD4202C, UTD4302C, UTD4204C, UTD4202CM, UPO2202CS, UPO2204CS
- Amount: 1PC



**UT-P06 Passive probe 300MHz**

- Probe factor: (1:1/10:1)
- Bandwidth: 300MHz
- Input resistance: 1×:1MΩ±2%, 10×:10MΩ±2%
- Working voltage: 1×:300Vpp, 10×:600Vpp
- Application: UTD4302C, UTD4304C, UTD4302CM
- Amount: 1PC



**UT-P07 Passive probe 500MHz**

- Probe factor: 10:1
- Bandwidth: 500MHz
- Input resistance: 10MΩ
- Working voltage: 1×:300Vpp, 10×:600Vpp
- Application:
- Amount: 1PC



**UT-V23 100:1 High voltage probe**

- Probe factor: 100:1
- Bandwidth: 100MHz
- Input resistance: 10MΩ±2%
- Working voltage: 2000Vpp
- Application: used for all oscilloscopes series
- Amount: 1PC



**UT-P20 Passive probe 250MHz 1500V**

- Bandwidth: 250MHz
- Attenuation: 100:1
- Maximum working voltage: 1500Vrms
- Application: UTD4000 series
- Amount: 1PC



**UT-P21 Passive high voltage probe 50MHz 15V**

- Bandwidth: 50MHz
- Attenuation: 1000:1
- Maximum working voltage: DC 15kVrms/AC 10kV(sine wave)
- Application: used for all UTD and UPO series oscilloscope
- Amount: 1PC



**UT-P30 Differential probe 100MHz 800V**

- Bandwidth: 100MHz
- Attenuation ratio: 100:1/10:1
- Input differential voltage: ±800Vpp
- Application: used for all UTD and UPO series oscilloscope
- Amount: 1PC

## UT-P/UT-T SERIES PROBES/THERMOCOUPLE



### UT-P31 High voltage differential probe 100MHz 1.5kV

- Bandwidth: 100MHz
- Attenuation ratio: 100:1/10:1
- Input differential voltage:  $\pm 1.5\text{kVpp}$
- Application: used for all UTD and UPO series oscilloscope
- Amount: 1PC



### UT-P32 Differential probe 50MHz 3kV

- Bandwidth: 50MHz
- Attenuation ratio : 1000:1/100:1
- Input differential voltage:  $\pm 3\text{kVpp}$
- Application: used for all UTD and UPO series oscilloscope
- Amount: 1PC



### UT-P33 Differential probe 120MHz 14kV

- Bandwidth: 120MHz
- Attenuation ratio : 100:1/10:1
- Input differential voltage:  $\pm 14\text{kVpp}$
- Application: used for all UTD and UPO series oscilloscope
- Amount: 1PC



### UT-P40 Current probe 100kHz 0.4A~60A

- Range : 50mV/A, 5mV/A
- Current range : 0.4A~60A
- Frequency range: DC~100kHz
- Maximum working voltage: 600Vrms
- Application: used for all UTD and UPO series oscilloscope
- Amount: 1PC



### UT-P41 Current probe 100kHz 0.05A~100A

- Range : 100mV/A, 10mV/A
- Current range : 50A~100A
- Frequency range: DC~100kHz
- Maximum working voltage: 600Vrms
- Application: used for all UTD and UPO series oscilloscope
- Amount: 1PC



### UT-T01 Thermocouple

- Accuracy:  $\pm 0.75\%$
- Test range:  $-40^{\circ}\text{C}\sim 260^{\circ}\text{C}$  ( $40^{\circ}\text{F}\sim 500^{\circ}\text{F}$ )
- Features and application: Teflon covered insulation, through hole input, used for general temperature measurement, not for liquid measurement
- Amount: 1PC



### UT-T03 Submersed thermocouple

- Probe length: 180mm
- Lead wire length: 1000mm
- Test range:  $-50^{\circ}\text{C}\sim 600^{\circ}\text{C}$  ( $58^{\circ}\text{F}\sim 1112^{\circ}\text{F}$ )
- Features and application: metal covers from head to handle, used for liquid and gel temperature measurement
- Amount: 1PC



### UT-T04 Through hole thermocouple

- Probe length: 180mm
- Lead wire length: 1000mm
- Test range:  $-50^{\circ}\text{C}\sim 600^{\circ}\text{C}$  ( $58^{\circ}\text{F}\sim 1112^{\circ}\text{F}$ )
- Features and application: metal covers from head to handle, used for food and other liquid or gel temperature measurement
- Amount: 1PC



### UT-T05 Gas thermocouple

- Probe length: 56mm
- Lead wire length: 1000mm
- Test range:  $-50^{\circ}\text{C}\sim 900^{\circ}\text{C}$  ( $58^{\circ}\text{F}\sim 1652^{\circ}\text{F}$ )
- Features and application: protected by stainless steel gas adjusting hole, used for air or gas temperature measurement, not for liquid temperature measurement
- Amount: 1PC



### UT-T06 Surface temperature thermocouple

- Probe length: 125mm
- Lead wire length: 1000mm
- Test range:  $-50^{\circ}\text{C}\sim 500^{\circ}\text{C}$  ( $58^{\circ}\text{F}\sim 932^{\circ}\text{F}$ )
- Features and application: aimed at flat or slightly convex surface, used for hot roller and vessel surface temperature measurement
- Amount: 1PC



## UT-T/UT-C SERIES THERMOCOUPLE/ALLIGATOR CLIP




### UT-T07 Surface temperature measuring thermocouple

- Probe length: 200mm
- Lead wire length: 1000mm
- Test range: -50°C~500°C (58°F~932°F)
- Features and application: probe bends for 90°, aimed at flat or slightly convex surface, used for hot roller and vessel surface temperature measurement
- Amount: 1PC



### UT-T10K Temperature probe

- Test range: -40°C~260°C (40°F~500°F)
- Accuracy: ±0.75%
- Features and application: used for UT213 series、UT39C、UT204A、UT206、UT208、UT208A、UT107、UT109、UT136C+、UT133A、UT89X、UT39C+
- Amount: 1PC



### UT-T12 Temperature probe

- Test range: 0°C-800°C (Error ±0.4%t)
- Features and application: Through hole input, used for UT323、UT321、UT322、UT325、UT181A
- Amount: 1PC



### UT-C01 Hook type test clamp

- Specifications: Rod length 62mm, hook can extend to 7.5mm
- Safety level: CAT III 1000V 10A
- Features: With safety handle and spring hook type alligator clips
- Amount: 1 pair



### UT-C02B (M4) threaded bore alligator clip

- Specifications: Length 80mm, opening 36mm
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Safety certificate: EN 61010-031:2015
- Amount: 1 pair



### UT-T09K Temperature probe

- Test range: -40°C~260°C (40°F~500°F)
- Accuracy: ±0.75%
- Features and application: crosshead socket type input, used for UT139C/E/S、UT216C/D、UT210D、UT213B/C、UT171B/C、UT219M、UT219DS、UT222
- Amount: 1PC



### UT-T11 Temperature probe

- Test range: -40°C~260°C (40°F~500°F)
- Accuracy: ±0.75%
- Features and application: through hole input, used for UT109、UT801、UT802、UT803、UT58 series、UT305 series、UT195M
- Amount: 1PC



### UT-T15 K-type temp clamp

- Test range: -40°C-200°C
- Jaw opening: 35mm
- Lead wire length: 2000mm
- Features and application: Flat plug for any K-type temperature recording meter
- Amount: 1 pair



### UT-C02A Through hole alligator clip

- Specifications: Length 80mm, opening 36mm
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Safety certificate: EN 61010-031:2015
- Amount: 1 pair



### UT-C04A Through hole alligator clip

- Specifications: Length 75mm, opening 27mm
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Safety certificate: EN 61010-031:2015
- Amount: 1 pair

## UT-C/UT-S SERIES

### ALLIGATOR CLIP/ADAPTER SOCKET



**UT-C05A (M4) threaded bore alligator clip (with protector)**

- Specifications: Length 67mm, opening 8.3mm
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Amount: 1 pair



**UT-C05B Through hole alligator clip (with protector)**

- Specifications: Length 71mm, opening 8.3mm
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Amount: 1 pair



**UT-C06 Test probes**

- Specifications: Rod length 106mm, probe length 19mm
- Safety level: CAT III 1000V 10A
- Features: Fully-insulated, with tip and protector, banana plug probes
- Amount: 1 pair



**UT-C07 Multifunctional electric test clips**

- Specifications: Rod length 110mm, adjustable clip length 8mm
- Safety level: CAT III 1000V/CAT IV 600V 5A
- Features: Standard transfer socket, adjustable multifunctional clips
- Amount: 1 pair



**UT-C08 Test probes**

- Specifications: Rod length 99mm, probe length 18mm
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Features: Fully-insulated, with tip and protector, straight type probes
- Amount: 1 pair



**UT-C09 Test probes**

- Specifications: Rod length 99mm, probe length 18mm
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Features: Fully-insulated, with tip and protector, lantern type probes
- Amount: 1 pair



**UT-C12 Through hole alligator clip (with protector)**

- Specifications: Length 53mm, opening 6mm
- Amount: 1 pair



**UT-S01A Multifunctional adapter socket**

- Function: Adapter test of temperature and capacitance
- Suitable product: UT804
- Amount: 1PC



**UT-S01B Multifunctional adapter socket**

- Function: Adapter test of temperature, capacitance and transistor
- Suitable products: UT803, UT58 series
- Amount: 1PC



**UT-S02B Multifunctional adapter socket**

- Function: Adapter test of temperature, capacitance and transistor
- Suitable products: UT61A, UT801, UT802
- Amount: 1PC



**UT-S03 Multifunctional adapter socket**

- Function: Adapter test of temperature and capacitance
- Suitable products: UT61B, UT61C, UT61D
- Amount: 1PC



**UT-S04 Multifunctional adapter socket**

- Function: Adapter test of temperature, capacitance and transistor
- Suitable product: UT61A (GS, 2010 CE version)
- Amount: 1PC

## UT-S/UT-W SERIES ADAPTER SOCKET/POWER ADAPTER



**UT-S05 Multipurpose standard adapter socket**

- Function: Adapter test of temperature and capacitance
- Suitable products: UT61B、 UT61C、 UT61D (GS version)
- Amount: 1PC



**UT-S06 Power adapter socket**

- Suitable products: UT171 series、 UT181
- Amount: 1PC



**UT-S07 Temperature adapter socket**

- Suitable product: UT181A
- Amount: 1PC



**UT-S08 UT612 adapter socket**

- Suitable products: UT611、 UT612
- Amount: 1PC



**UT-S09 BNC test wire adapter socket**

- Suitable product: UT81 series
- Amount: 1PC



**UT-S10 Wattmeter adapter socket**

- Fixed current: 10A
- Suitable product: UT71E
- Amount: 1PC



**UT-W01 Power adapter**

- Input: AC100~240V 50/60Hz
- Output: DC9V 4A
- Certification: ErP
- Suitable products: UTS1000 series、 UTD1000 series、 UT283A、 EDU1000
- Amount: 1PC



**UT-W03 Power adapter**

- Input: AC230V 50/60Hz 65mA
- Output: DC14.5V 600mA
- Certification: ErP
- Suitable products: UT512、 UT511
- Amount: 1PC



**UT-W04 Power adapter**

- Input: AC230V 50/60Hz
- Output: DC14.5V+0.5V 1.0A
- Certification: ErP
- Suitable products: UT513、 UT513A
- Amount: 1PC



**UT-W05 Power adapter**

- Input: 100~240V 50/60Hz
- Output: DC9V 4A outer positive inside negative
- Certification: ErP
- Suitable products: UT620A、 UT620B
- Amount: 1PC

## UT-W/UT-D SERIES POWER ADAPTER/DATA CABLE



### UT-W06 Power adapter

- Input: AC230V/50Hz
- Output: DC6.0V/450mA
- Certification: ErP
- Suitable product: UT81 series
- Amount: 1PC



### UT-W08 Power adapter

- Input: AC230V 50Hz
- Output: DC6V/450mA
- Certification: ErP
- Suitable products: UT305A、UT305C
- Amount: 1PC



### UT-W10 Power adapter

- Input: AC230V 50/60Hz
- Output: DC9V 0.2A
- Certification: ErP
- Suitable products: UT801 (2010 CE)、UT802 (2010 CE)
- Amount: 1PC



### UT-D02+ RS232C data cable

- Wire length: 1m
- Features: RS232C interface, one-way transmission
- Suitable products: UT61 series、UT109
- Amount: 1PC



### UT-D05 RS232C data cable

- Wire length: 1m
- Features: RS232C interface, two-way transmission
- Suitable products: UT70C、UT70D
- Amount: 1PC



### UT-W07 Power adapter

- Input: AC100~240V 50/60Hz
- Output: DC10V 500mA input short-circuit protection
- Certification: ErP
- Suitable products: UT181A、UT171B/C
- Amount: 1PC



### UT-W09 Power adapter

- Input: AC220V 50Hz
- Output: DC9V 0.2A
- Certification: ErP
- Suitable products: UT801、UT802
- Amount: 1PC



### UT-D01 RS232C data cable

- Wire length: 1m
- Features: RS232C interface, one-way transmission
- Suitable products: UT70B
- Amount: 1PC



### UT-D04 USB data cable

- Wire length: 1m
- Features: USB interface, one-way transmission
- Suitable products: UT71 series、UT230 series、UT61B/C/D
- Amount: 1PC



### UT-D09 USB data cable

- Wire length: 1m
- Features: USB interface, two-way transmission
- Suitable products: UT171 series、UT243、UT181A
- Amount: 1PC

## UT-D/UT-M SERIES DATA CABLE/CONVERTER



**UT-D10 USB data cable**

- Wire length: 1m
- Features: USB interface, two-way transmission
- Suitable products: UT81B、UT81C
- Amount: 1PC



**UT-D12 USB charging line**

- Wire length: 0.5m
- Material: 2 cores 24# wire
- Suitable products: LM600、LM800、LM1000、LM1200、LM1500、A25M、A25D、A25F、A37
- Amount: 1PC



**UT-D14 USB 2.0 dual-head printer line**

- Wire length: 1.5m
- Suitable products: UTD2000 series、UTD4000 series、UPO2102CS、UPO2202CS、UPO2104CS、UPO2204CS、UTG2025A
- Amount: 1PC



**UT-D16 USB single-head connecting wire**

- Wire length: 1m
- Suitable product: UT171C
- Amount: 1PC



**UT-D18 USB dual header standard connecting wire**

- Wire length: 1m
- Suitable products: UT620A、UT620B
- Amount: 1PC



**UT-D11 USB connecting wire**

- Wire length: 1m
- Suitable products: UT305A、UT305C、UT315、UT321、UT322、UT325、UT331、UT332、UT382、UT612、UT323、UT362
- Amount: 1PC



**UT-D13 USB standard printer line**

- Wire length: 1m
- Suitable products: UT372、UT512、UT513A、UT803、UT804、UT805A
- Amount: 1PC



**UT-D15 USB2.0 communication cable**

- Wire length: 1.5m
- Suitable products: UTD2025CL、UTD2052CL
- Amount: 1PC



**UT-D17 USB2.0 data cable**

- Features: one head for HOST, the other for MINI-USB
- Wire length: 1.5m
- Suitable products: UT283A、UTD1025CL、UTD1050CL、UTD1025DL、UTD1050DL
- Amount: 1PC



**UT-M03 Voltage/current converter**

- Range: 4mA/6mA, 40mA/60mA, 400mA/600mA
- Suitable products: UTD1000C、UTD4000C series
- Amount: 1PC



## UT-W/UT-D SERIES POWER ADAPTER/DATA CABLE



### UT-M04 Voltage/current converter

- Range: 4A/6A
- Suitable products: UTD1000C、UTD4000C series
- Amount: 1PC



### UT-M08 Lithium battery subassembly

- Output voltage: 7.4V
- Capacity: 3600mAh
- Suitable products: UTD1000L series、UT283A
- Amount: 1PC



### UT-M10 Voltage/current converter

- Range: uA, 40mA, 400mA
- Suitable products: UTD1025DL、UTD1050DL、UTD1025CL、UTD1050CL
- Amount: 1PC



### UT-D07A Bluetooth adaptor

- Description: Bluetooth 4.0 communication protocol
- Support: iOS 6.0 or above, Android 4.0 or above
- Application: UT71、UT171、UT181 series
- Power: 1.5V battery (R03) x 2



### UT-M07 10A current diverter

- Range: 10A
- Suitable products: UTD1025CL、UTD1052CL、UTD1050CL
- Amount: 1PC



### UT-M09 Logic analyzer module

- Channels: 16
- Sampling rate: 250MS/s
- Maximum input voltage:  $\pm 40V_{pp}$
- Trigger mode: Time trigger, array trigger
- Suitable products: UTD4000CM、UPO2000CS
- Amount: 1PC



### UT-U01 Logic analyzer module

- Channels: 16
- Maximum input voltage:  $\pm 40V_{pk}$
- Minimum voltage swing: 1.2Vpp
- Suitable products: UTD4000C series
- Amount: 1PC



### UT-U02 Digital protocol cable

- Channels: 16
- Suitable products: UTG4000A series
- Amount: 1PC

