



EN 61010-1
EN 61326-1



■ UT58A



■ UT58B



■ UT58C

SPECIFICATIONS

Specifications	Range	Best Accuracy		
		UT58A	UT58B	UT58C
Model		UT58A	UT58B	UT58C
DC Voltage(V)	200mV/2V/20V/200V/1000V	±(0.5%+1)	±(0.5%+1)	±(0.5%+1)
AC Voltage(V)	2V/20V/200V/750V	±(0.8%+3)	±(0.8%+3)	±(0.8%+3)
DC Current(A)	20µA/2mA/20mA/200mA/20A	±(0.8%+1)		
	2mA/20mA/200mA/20A		±(0.8%+1)	
AC Current(A)	2mA/200mA/20A			±(0.8%+1)
	2mA/200mA/20A	±(1%+3)	±(1%+3)	±(1%+3)
Resistance(Ω)	200Ω/2kΩ/20kΩ/2MΩ/20MΩ/200MΩ	±(0.8%+1)	±(0.8%+1)	
	200Ω/2kΩ/20kΩ/2MΩ/20MΩ			±(0.8%+1)
Capacitance (F)	2nF/200nF/100µF	±(4%+3)	±(4%+3)	±(4%+3)
Frequency (Hz)	2kHz/20kHz			±(1.5%+5)
Temperature (°C)	-40°C~1000°C		±(1%+3)	±(1%+3)
Features				
Display Count		2000	2000	2000
Manual Range		✓	✓	✓
Diode		✓	✓	✓
Transistor		✓	✓	✓
Auto Power Off		✓	✓	✓
Continuity Buzzer		✓	✓	✓
Data Hold		✓	✓	✓
Low Battery Indication		✓	✓	✓
Full Icon Display		✓	✓	✓
Input Impedance for DCV	Around 10MΩ	✓	✓	✓
Test Lead Connection Indications		✓	✓	✓

GENERAL CHARACTERISTICS

Power	9V Battery(6F22)
LCD Size	60 × 54 mm
Product Color	Red and Grey
Product Net Weight	350 g (Including holster)
Product Size	179mm × 88mm × 39mm
Standard Accessories	UT58A-Battery, Test Lead,Holster,Multi-Purpose Socket
	UT58B/UT58C-Battery, Test Lead,Holster,Multi-Purpose Socket, Point ContactTemperature Probe
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	44 PCs
Standard Carton Measurement	705×450×340mm (0.11 CBM Per Standard Carton)
Standard Carton Gross Weight	27 Kg



EN 61010-1
EN 61326-1



UT58D



UT58E

SPECIFICATIONS



Specifications	Range	Best Accuracy	
Model		UT58D	UT58E
DC Voltage(V)	200mV/20V/200V/1000V	±(0.5%+1)	
	200mV/2V/20V/200V/1000V		±(0.05%+3)
AC Voltage(V)	2V/200V/1000V	±(0.8%+3)	
	2V/20V/200V/1000V		±(0.5%+10)
DC Current(A)	2mA/200mA/20A	±(0.8%+1)	±(0.5%+5)
	2mA/200mA/20A	±(1%+3)	
AC Current(A)	20mA/200mA/20A		±(0.8%+10)
	200Ω/2kΩ/200kΩ/2MΩ/20MΩ	±(0.8%+1)	
Resistance(Ω)	200Ω/2kΩ/20kΩ/2MΩ/20MΩ		±(0.3%+1)
	20nF/200nF/2μF/100μF	±(2.5%+5)	
Capacitance (F)	2nF/20nF/2μF/20μF		±(3%+40)
	2mH/20mH/200mH/20H	±(2%+10)	
Inductance (H)	20kHz		±(1.5%+5)
Frequency (Hz)	-40 °C~1000 °C		±(1%+30)
Temperature (°C)			
Features			
Display Count		2000	20000
Manual Range		✓	✓
Diode		✓	✓
Transistor		✓	✓
Auto Power Off		✓	✓
Continuity Buzzer		✓	✓
Data Hold		✓	✓
Low Battery Indication		✓	✓
Full Icon Display		✓	✓
Input Impedance for DCV	Around 10MΩ	✓	✓
Test Lead Connection Indications		✓	✓

GENERAL CHARACTERISTICS

Power	9V Battery(6F22)
LCD Size	60mm × 54mm
Product Color	Red and Grey
Product Net Weight	350 g (Including holster)
Product Size	179mm×88mm×39mm
Standard Accessories	UT58D-Battery, Test Lead,Holster,Muli-Purpose Socket
	UT58E-Battery, Test Lead,Holster,Muli-Purpose Socket,Point Contact Temperature Probe
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	44 PCs
Standard Carton Measurement	705mm × 450mm × 340mm (0.11 CBM Per Standard Carton)
Standard Carton Gross Weight	27.6 Kg