

# UT522

# Earth Ground Testers



[Enlarge](#)

[Download Manual](#)

[Download Software](#)

## SPECIFICATIONS

| Basic Functions              | Range   | Best Accuracy                             |
|------------------------------|---|---|
| Earth Resistance Testing     | 0 ~ 40Ω<br>0 ~ 400Ω<br>0 ~ 4000Ω                | ±2%rdg±0.2Ω<br>±2%rdg±3dgt<br>±2%rdg±3dgt |
| Earth Voltage Testing        | 0~400Vac(50/60Hz)                               | ±1%rdg±6dgt                               |
| Special Functions            |   |   |
| Data Hold                    |   | ✓   |
| Backlight Display            |   | ✓   |
| Data Logging                 | 20  | ✓   |
| Battery Check                |   | ✓   |
| Sleep Mode                   | Around 10 Minutes                               | ✓   |
| Full Icon Display            |   | ✓   |
| Over-range Display           | Display "OL"                                    | ✓   |
| Contact Badness Display      | C Port or E Port don't contact Display"- - - Ω" | ✓   |
| Simple 2-Wires Testing       |   | ✓   |
| Precision 3-Wires Testing    |   | ✓   |
| Double Insulation Protection |   | ✓   |

## GENERAL CHARACTERISTICS

|                              |   |
|------------------------------|---|
| Power                        | 1.5V Alkaline Battery(AA) x 6   |
| LCD Size                     | 70.6 mm x 34 mm   |
| Product Color                | Grey  |
| Product Net Weight           | 560g  |
| Product Size                 | 160 x 100 x 70.5 mm   |
| Standard Accessories         | Battery, Three Test Lead (Green + Yellow + Red), English Manual, Simple Test Lead, Carrying Bag, Test Probe 2 pcs |
| Standard Individual Packing  | Gift Box  |
| Standard Quantity Per Carton | 4 pcs   |
| Standard Carton Measurement  | 615 x 530 x 190 mm (0.062 CBM Per Standard Carton)  |
| Standard Carton Gross Weight | 15kg  |

\*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)