

pH600/CD600/CD601/CD610/CD611/CD97 pH/EC & TDS Economical Pocket Testers

CE









Milwaukee's economical testers are easy-to-use and low cost instruments to measure quick and reliable pH, EC or TDS values.

Measuring electrical conductivity is the best way of checking the amount of salt or dissolved solids (TDS) in water. Milwaukee provides you with a range of pocket testers that will allow you to measure from very low to very high conductivity solutions.

All EC/TDS testers compensate for the temperature variance automatically.



Specifications	 pH600	 CD600	 CD601
Range	0.0 to 14.0 pH	0 to 1990 ppm	0 to 1990 µS/cm
Resolution	0.1 pH	10 ppm	10 µS/cm
Accuracy	±0.1 pH	±2% Full scale	±2% Full scale
Calibration	manual, 1 point	manual, 1 point	manual, 1 point
Temperature Compensation		automatic from 5 to 50°C	automatic from 5 to 50°C
Environment	0 to 50°C / 32 to 122°F; max RH 95%	0 to 50°C / 32 to 122°F; max RH 95%	0 to 50°C / 32 to 122°F; max RH 95%
Battery Type / Battery Life	3 x 1.5V alkaline / 700 hours of use	4 x 1.5V alkaline / 350 hours of use	4 x 1.5V alkaline / 350 hours of use
Packaging dimensions	180 x 65 x 32 mm	180 x 65 x 32 mm	180 x 65 x 32 mm
Packaging weight	120 g	120 g	120 g

Specifications	 CD610	 CD611	 CD97
Range	0 to 10000 ppm	0 to 20000 µS/cm	0 to 1000 ppm
Resolution	100 ppm	100 µS/cm	1 ppm
Accuracy	±2% Full scale	±2% Full scale	±10 ppm
Calibration	manual, 1 point	manual, 1 point	manual, 1 point
Temperature Compensation		automatic from 5 to 50°C	automatic from 5 to 50°C
Environment	0 to 50°C / 32 to 122°F; max RH 95%	0 to 50°C / 32 to 122°F; max RH 95%	0 to 50°C / 32 to 122°F; max RH 95%
Battery Type / Battery Life	4 x 1.5V alkaline / 350 hours of use	4 x 1.5V alkaline / 350 hours of use	4 x 1.5V alkaline / 350 hours of use
Packaging dimensions	180 x 65 x 32 mm	180 x 65 x 32 mm	180 x 65 x 32 mm
Packaging weight	120 g	120 g	120 g

Accessories

- M10004B** pH 4.01 buffer solution 20 mL sachet (25 pcs)
- M10007B** pH 7.01 buffer solution 20 mL sachet (25 pcs)
- M10010B** pH 10.01 buffer solution, 20 mL sachet (25 pcs)
- M10030B** 12880 µS/cm calibration solution, 20 mL (25 pcs)

- M10031B** 1413 µS/cm calibration solution, 20 mL (25 pcs)
- M10032B** 1382 ppm (mg/L) calibration solution, 20 mL (25 pcs)
- M10038B** 6.44 ppt (g/L) calibration solution, 20 mL (25 pcs)
- MA9015** Electrode storage solution, 230 mL
- MA9016** Electrode cleaning solution, 230 mL



Ordering Information

pH600, CD600, CD601, CD610, CD611 and CD97 are supplied in a plastic hard carrying case, complete with protective cap, calibration screwdriver, batteries and instructions.