



- ▷ For heavy industrial applications
- ▷ Favored by shipyards and power plants
- ▷ Noise free using new high technology materials
- ▷ Fast and easy coil replacement
- ▷ IP20 protection
- ▷ Made in Korea, by HYUNDAI heavy industries
- ▷ Standards: IEC60947, UL508, CE, Lloyd's register

TYPE	RATING (KW) AC3	AMPERE (A) AC3	AMPERE (A) AC1	AUX. CONTACT NO / NC	CODE					
					230V AC	400V AC	440V AC	110V AC	48V AC	24V AC
HiMC 9	4	9	20	1 + 1	044.10.010	044.12.010	044.14.010	044.16.010	044.18.010	044.20.010
HiMC 12	5.5	12	20	1 + 1	044.10.020	044.12.020	044.14.020	044.16.020	044.18.020	044.20.020
HiMC 18	7.5	18	25	1 + 1	044.10.030	044.12.030	044.14.030	044.16.030	044.18.030	044.20.030
HiMC 22	11	22	32	1 + 1	044.10.040	044.12.040	044.14.040	044.16.040	044.18.040	044.20.040
HiMC 32	15	32	50	2 + 2	044.10.050	044.12.050	044.14.050	044.16.050	044.18.050	044.20.050
HiMC 40	18.5	40	50	2 + 2	044.10.060	044.12.060	044.14.060	044.16.060	044.18.060	044.20.060
HiMC 50	22	50	70	2 + 2	044.10.070	044.12.070	044.14.070	044.16.070	044.18.070	044.20.070
HiMC 65	30	65	100	2 + 2	044.10.080	044.12.080	044.14.080	044.16.080	044.18.080	044.20.080
HiMC 80	37	80	110	2 + 2	044.10.090	044.12.090	044.14.090	044.16.090	044.18.090	044.20.090
HiMC 90	45	90	135	2 + 2	044.10.100	044.12.100	044.14.100	044.16.100	044.18.100	044.20.100
HiMC 110	55	110	150	2 + 2	044.10.110	044.12.110	044.14.110	044.16.110	044.18.110	044.20.110
HiMC 130	65	130	160	2 + 2	044.10.120	044.12.120	044.14.120	044.16.120	044.18.120	044.20.120
HiMC 150	75	150	200	2 + 2	044.10.130	044.12.130	044.14.130	044.16.130	044.18.130	044.20.130
HiMC 180	90	180	230	2 + 2	044.10.140	044.12.140	044.14.140	044.16.140	044.18.140	044.20.140
HiMC 220	110	220	260	2 + 2	044.10.150	044.12.150	044.14.150	044.16.150	044.18.150	044.20.150
HiMC 260	132	260	300	2 + 2	044.10.160	044.12.160	044.14.160	044.16.160	044.18.160	044.20.160
HiMC 300	160	300	350	2 + 2	044.10.170	044.12.170	044.14.170	044.16.170	044.18.170	044.20.170
HiMC 400	220	400	450	2 + 2	044.10.180	044.12.180	044.14.180	044.16.180	044.18.180	044.20.180
HiMC 500	250	500	550	2 + 2	044.10.190	044.12.190	044.14.190	044.16.190	044.18.190	044.20.190
HiMC 630	330	630	750	2 + 2	044.10.200	044.12.200	044.14.200	044.16.200	044.18.200	044.20.200
HiMC 800	440	800	900	2 + 2	044.10.210	044.12.210	044.14.210	044.16.210	044.18.210	044.20.210

▷ Also available: 24V DC and 48V DC