

testo 317-3 For accurate and reliable CO detection.

The testo 317-3 CO monitor provides fast and easy ambient carbon monoxide testing. This low cost ambient CO air quality tester measures and displays CO from 0-1999 PPM and gives warning of excessive levels with adjustable audible and visual alarms.

Other handy features include: HOLD and MAX settings, and an exclusive self-check mode that verifies CO sensor response in seconds. This pocket-sized CO meter weighs only 9 ounces and can be ordered in kits that include the meter, a softcase (with belt loop), earphone, wrist strap, two AAA batteries and an instruction manual. Have confidence in your readings thanks to a three-year sensor warranty, standard.

Features:

Three CO sensor year warranty

Visual and audible alarm warns you of dangerous CO concentrations.

No zeroing required! The self-check function verifies accurate CO measurement.

Adjustable alarm threshold

Self-test mode verifies CO sensor function anytime, anywhere with the need for test gas.

Programmable high and low alarm options.

Easily clips to your belt for hands-free convenience.

Earphone jack for loud environments.



The testo 317-3 comes with an earphone jack for loud environments.

CO detection For contractors and building inspectors.

The testo 317-3 CO monitor detects the presence of carbon monoxide (CO) in ambient air and warns the user both visually and audibly about dangerous CO concentrations during furnace and boiler service and maintenance, weatherization audits or home inspections.

Take it with you to detect the presence of carbon monoxide in ambient air during furnace and boiler service and maintenance, weatherization audits or during home inspections. Self-test mode verifies CO sensor at all times without the need for test gas.

For residential and commercial combustion applications

Have confidence in your ambient CO detection.



Leak detection for all your HVAC/R needs.



Gas leak detection:



testo 317-2.

Gas leak detector for easy checks on gas pipe connections, with visual bar display. The 317-2 shows gas concentration in a visual bar-style display. The unit's sensor conducts a self-test after turning on and an audible alarm confirms the instrument is ready for use. If the alarm sounds and continues to increase in volume, potentially unsafe gas concentrations are being reached. A continuous alarm will sound when the threshold has been exceeded.

Refrigerant leak detection:



testo 316-3.

The testo 316-3 is a reliable refrigerant leak detector that delivers dependable, rugged performance at a great value. The proven heated diode sensor provides great sensitivity down to 0.15 ounces/year including the new refrigerant blends like R-410A, R-407C, and R-134a. Just turn it on and start getting readings immediately! Thanks to the automatic zeroing, the testo 316-3 is extremely fast and can be used even in previously contaminated areas.

testo 317-3 kit information

Professional Kit:	Part No.
Includes: testo 317-3 with self-test function, earphone, leather holster with belt clip and wrist strap.	0632 3173

Specifications:

Description:	
Measuring range:	0 to 1,999 ppm CO
Resolution:	1 ppm
Accuracy:	±5%
Reaction time (t 90):	40 seconds
Battery type:	23 to 113 °F
Battery life:	150 hours (with alarm off)
Instrument warranty:	2 years
CO sensor warranty:	3 years
Dimensions:	1.5" x 6"



For more information about Testo's complete line of combustion analyzers and CO detectors go to:

www.testo.com/combustion

testo 317-3.

Reliable CO detection.

Testo, Inc.
40 White Lake Road
Sparta, NJ 07871
Phone: 800-227-0729
Fax: 862-354-5020
e-mail: info@testo.com